

Technical Data Sheet

Product name:

Rockcote Cerano Texture

Description:

ROCKCOTE Cerano is a flexible acrylic based coating manufactured using 100% acrylic emulsions, quality graded quartz and other additives blended together to provide a natural coloured render finish over many substrates. ROCKCOTE Cerano provides a seamless and natural solid rendered look, with the flexibility and performance required for all solid masonry substrates and modern lightweight walling systems.

Features

- Water based
- Ease of Use
- Vapour permeable

Benefits

- Tough
- Flexible
- Water resistant
- Excellent Adhesion
- Long term exterior protection
- Premixed product, just stir and apply

Typical Use:

- ROCKCOTE Cerano is suitable for application over properly prepared substrates such as brick, block, concrete, A.A.C Panels/blocks and plasterboard
- Can be used interior and exterior
- Must be over coated with Resene Solventborne Aquapel

Limitations:

- Check colour before use
- Ensure same batch numbers are used on a single wall where possible
- Should not be applied in temperatures below 5°C or above 35°C
- Not suitable for areas of continual damp or areas submerged in water

Technical Data:

Typical Data at 25°C and 50% Relative Humidity

Coverage:	2 to 2.5 sq meters per litre (for 2 coats completed)
Substrates:	all prepared base coats of plaster
Abrasive strength:	Excellent

Adhesion:	Excellent
Vapour Permeability:	No vapour barrier formed
VOC:	N/A
Colour:	white (untinted)
Packaging:	15 Ltr & 4 Ltr Pails
Clean up:	Water while product is wet
Use by:	12months from date of manufacture
Storage:	Cool, dry place, of the ground
Application Temperature:	+ 5 °C to + 35 °C
Usual No Coats:	2
Drying Time:	72 hours- 1 week
Touch Dry:	2 hours
Dry to Recoat:	4 hours
Film Build:	Approximately 0.25mm dry film build per coat
Thinning:	Up to 5%

Surface Preparation:

ROCKCOTE Cerano must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants. Substrates must not contain more than 15% moisture prior to application. Do not apply if air and surface temperatures are below 5°C or above 35°C. Must be applied over the top of ROCKCOTE Polymer Render. When applied over Fibre Cement Sheet then RMaxx must be used.

Mixing:

Mix until consistent before applying

Application:

Check colour before use. Ensure the same batch numbers are used on a single wall where possible. Mix to help reactivate and aerate contents. Apply evenly over the properly prepared substrate with a hawk and trowel. Ideally apply slightly thicker than the sand granules to achieve optimum results. Finish with a steel or Venetian trowel. Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions. If joining up to the previous day's application, it is "good working practice" to start and finish on an external or internal corner. Keep sheltered from rain & moisture for 24 - 48 hrs after completion dependent on climatic conditions.

Clean up:

Wash equipment and spills as soon as possible with water.

Environmental and Safety

Ensure washing water does not enter waterways. Wet waste should be disposed of in empty bags/buckets, once dry dispose of in trade waste. The wet compound is Alkaline and prolonged skin contact should be avoided. Wear rubber gloves, dust masks and safety glasses when handling products.

Material Safety Data Sheets are available upon request or access directly from
<https://reseneconstruction.co.nz/technical-library/safety-data-sheets/>